

T1000 Product Description



The T1000 is a satellite only unit. There is no cellular required to use the T1000. It is designed to be used in a remote location or to monitor assets. It is a battery operated device that will last for 7 years with 2 locates per day.

Key features include:

- Multi-year battery life
- 7 years at 2 reports per day
- Reporting from every 30 minutes to once per day to once every 45 days
- No External power needed
- Seamless Satellite Coverage in
 - North America
 - Europe
 - Middle East
- Quick and simple installation
- Scheduled or event driven reports

Alarms

The T1000 has capabilities to monitor up to 4 different alarms. These alarms can be used to monitor PTO's, Power disconnect, Door monitoring, etc... Utilizing an alarm cable these monitoring capabilities are available to the user.

Installation

Installation is as easy as using the double sided tape (the unit's case will be damaged if pried from the tape) or fastening with screws through the units mounting holes. The only requirement is the unit must be able to see the sky during normal operations of the asset.

Locates

The T1000 comes equipped with up to 12 locates per day, if more locates are preferred an additional cost will be associated. The amount of daily locates will affect the battery life of the unit. Standard battery life is 2 ½ years for 6 locates a day.

Battery

The Battery life of the hardware depends on the amount of locates that the unit is programmed for. The more locate per day the less battery life

the unit will have. Batteries are easily replaceable in the field and take only minutes. The T1000 will also display battery life every message that it sends. This way a user can prepare to change the battery when needed.

Interval Override

Interval override allows the unit to start to send locates more frequently if an alarm input is detected. Locates can be sent up to 5 minutes for a certain duration of time (1 hour to 1 day). Interval override allows for better monitoring in case of theft, power failure or door sensor.

“Can not”

The T1000 can not be located on demand. Every unit needs to be pre-programmed with locates and alarms before being shipped. Locates can not be changed in the field. Customer will have to ship unit back to be reprogrammed to the new configuration. Geo-Fencing is currently not available but may become available in the future.

Specification

- Size: 7.25 x 3.25 x 1 inch
- Weight: 13 ounces
- Mounting: Adhesive Tape, Screws
- Power: Internal Battery, 12-24 Volt Automotive Line Power
- Antennas: Internal



Coverage Map

